ISOTERMINAL

PCR Series Quick Terminal Blocks

①Electrical parameter:450V/4KV/32A

②Stripping length: =10-12mm

③Applicable conductor:0.5-4mm²
(Universal use of soft and hard cables)



PCT-5224 PCT-5226



PCT-5211D PCT-5222D PCT-5233D
PCT-5224D PCT-5226D



PCT-512 PCT-513
PCT-514 PCT-515



PCT-512G PCT-513G
PCT-514G PCT-515G



PCT-5212 PCT-5213
PCT-5214 PCT-5215

Mimi Wiring Terminal

Electrical parameter: 450V/32A

Stripping length: 10mm

Applicable conductor: 0.2-4.0mm²(Single/multi strand hardwire)0.2-4.0mm²(Multi strand flexible wire)



PCT-5222
PCT-5222G PCT-5222D



PCT-5233
PCT-5233G PCT-5233D



PCT-5244
PCT-5244G PCT-5244D



PCT-5255
PCT-5255G PCT-5255D



PCT-5266
PCT-5266G PCT-5266D



PCT-5288
PCT-5288G PCT-5288D



PCT-521010
PCT-521010G PCT-521010D



PCT-521012
PCT-521012G PCT-521012D

1 Series quick wiring terminals

①Electrical parameter: 250V/4KV/24A	250V/4KV/24A
②Stripping length: 10-12mm	10-12mm
③Applicable conductor: 0.75-2.5mm²Dedicated for hard wires)	0.75-4mm²



PCT-102



PCT-104



PCT-106



PCT-108



PCT-604